

TIPO PISTONE	VELOCITA' PISTONE m/sec									
-----------------	-------------------------	--	--	--	--	--	--	--	--	--

TRE ELEMENTI	176/3	0.26	0.30	0.34	0.38	0.41	0.45				
	150/3	0.36	0.41	0.47	0.53	0.56	0.62				
	127/3	0.50	0.58	0.66	0.73	0.79	0.87				
	107/3	0.70	0.81	0.92	1.04				
	98/3	0.84	0.97				
	75/3				
	58/3				

DUE ELEMENTI	205/2	0.19	0.22	0.25	0.28	0.30	0.33				
	170/2	0.28	0.32	0.37	0.41	0.44	0.48				
	141/2	0.40	0.47	0.53	0.60	0.64	0.70				
	120/2	0.56	0.65	0.74	0.82	0.88	0.97				
	103/2	0.76	0.88	1.00	1.12				
	85/2	1.12				
	77/2				
	60/2				
	46/2				

NORMALI	280	0.10	0.12	0.13	0.15	0.16	0.18				
	238	0.14	0.16	0.19	0.21	0.22	0.25				
	230	0.15	0.17	0.20	0.22	0.24	0.26				
	200	0.20	0.23	0.26	0.30	0.32	0.35				
	180	0.25	0.29	0.33	0.37	0.39	0.43				
	150	0.36	0.41	0.47	0.53	0.56	0.62				
	130	0.48	0.55	0.63	0.70	0.75	0.83				
	120	0.56	0.65	0.74	0.82	0.88	0.97				
	110	0.67	0.77	0.87	0.98				
	100	0.80	0.93				
	90	1.00				
				
				

L/min	380	440	500	560	600	660	---	---	---	---
-------	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

potenza / pressione massima	kw Mpa	kw Mpa	kw Mpa	kw Mpa	kw Mpa	kw Mpa	kw Mpa	kw Mpa	kw Mpa	kw Mpa
	15 2.2	15 1.9	18.5 2.0	18.5 1.8	18.5 1.7	22 1.7				
	18.5 2.7	18.5 2.3	22 2.4	22 2.1	22 1.9	30 2.5				
	22 3.2	22 2.7	30 3.3	30 3.0	30 2.8	37 3.0				
	30 4.4	30 3.8	37 4.0	37 3.6	37 3.3	45 3.7				
	37 5.0	37 4.6	45 4.9	45 4.4	45 4.1	55 4.5				
	45 5.0		55 5.0	55 5.0	75 5.0					

Tipo Centralina	02/E - 2"									
-----------------	-----------	--	--	--	--	--	--	--	--	--

I valori di pressione in tabella possono essere aumentati del 10% per perdite dinamiche
1 MPa = 10 bar

**TABELLA VELOCITA' E POTENZE
CENTRALINE 02/E - 2"**



Start Elevator

05 302 / I

rev. 0

1/2

TIPO PISTONE	VELOCITA' PISTONE m/sec						
--------------	-------------------------	--	--	--	--	--	--

TRE ELEMENTI	176/3	0.51	0.60	0.68	0.76	0.82	0.90
	150/3	0.70	0.83	0.94	1.05
	127/3	0.97	1.15
	107/3
	98/3
	75/3
	58/3

DUE ELEMENTI	205/2	0.37	0.44	0.50	0.56	0.60	0.66
	170/2	0.54	0.64	0.73	0.82	0.88	0.96
	141/2	0.79	0.94	1.07
	120/2	1.09
	103/2
	85/2
	77/2
	60/2
	46/2

N O R M A L I	280	0.20	0.24	0.27	0.30	0.32	0.36
	238	0.28	0.33	0.37	0.42	0.45	0.49
	230	0.30	0.35	0.40	0.45	0.48	0.53
	200	0.39	0.46	0.53	0.59	0.63	0.70
	180	0.49	0.57	0.65	0.73	0.78	0.86
	150	0.70	0.83	0.94	1.05
	130	0.93	1.10
	120	1.09
	110
	100
	90

L/min	740	880	1000	1120	1200	1320
-------	------------	------------	-------------	-------------	-------------	-------------

potenza / pressione massima	kw Mpa	kw Mpa	kw Mpa	kw Mpa	kw Mpa	kw Mpa
	30 2.2	30 1.9	37 2.0	37 1.8	37 1.7	48 1.7
	37 2.7	37 2.3	44 2.4	48 2.1	48 1.9	60 2.5
	44 3.2	44 2.7	60 3.3	60 3.0	60 2.8	74 3.0
	60 4.4	60 3.8	74 4.0	74 3.6	74 3.3	90 3.7
	74 5.0	74 4.6	90 4.9	90 4.4	90 4.1	110 4.5
	90 5.0		110 5.0	110 5.0	150 5.0	
Tipo Centralina	02/E - 2" 2MP					

1 MPa = 10 bar

I valori di pressione in tabella possono essere aumentati del 10% per perdite dinamiche

**TABELLA VELOCITA' E POTENZE
CENTRALINE 02/E - 2"**



Start Elevator

05 302 / I

rev. 0

2/2