

TIPO PISTONE	VELOCITA' PISTONE m/sec									
-----------------	-------------------------	--	--	--	--	--	--	--	--	--

TRE ELEMENTI	176/3	0.26	0.30	0.34	0.38	0.41	0.45				
	150/3	0.36	0.41	0.47	0.53	0.56	0.62				
	127/3	0.50	0.58	0.66	0.73	0.79	0.87				
	107/3	0.70	0.81	0.92	1.04				
	98/3	0.84	0.97				
	75/3				
	58/3				

DUE ELEMENTI	205/2	0.19	0.22	0.25	0.28	0.30	0.33				
	170/2	0.28	0.32	0.37	0.41	0.44	0.48				
	141/2	0.40	0.47	0.53	0.60	0.64	0.70				
	120/2	0.56	0.65	0.74	0.82	0.88	0.97				
	103/2	0.76	0.88	1,00	1.12				
	85/2	1.12				
	77/2				
	60/2				
	46/2				

N O R M A L I	280	0.10	0.12	0.13	0.15	0.16	0.18				
	238	0.14	0.16	0.19	0.21	0.22	0.25				
	230	0.15	0.17	0.20	0.22	0.24	0.26				
	200	0.20	0.23	0.26	0.30	0.32	0.35				
	180	0.25	0.29	0.33	0.37	0.39	0.43				
	150	0.36	0.41	0.47	0.53	0.56	0.62				
	130	0.48	0.55	0.63	0.70	0.75	0.83				
	120	0.56	0.65	0.74	0.82	0.88	0.97				
	110	0.67	0.77	0.87	0.98				
	100	0.80	0.93				
	90	1.00				
				
				

L/min	380	440	500	560	600	660	---	---	---	---
-------	------------	------------	------------	------------	------------	------------	-----	-----	-----	-----

potenza / pressione massima	kw Mpa	kw Mpa	kw Mpa	kw Mpa	kw Mpa	kw Mpa	kw Mpa	kw Mpa	kw Mpa	kw Mpa
	16 1.7	20 2.0	24 1.9	24 1.6	29 2.0	29 1.8				
	20 2.3	24 2.4	29 2.4	29 2.1	33 2.2	33 2.0				
	24 2.8	29 2.8	33 2.7	33 2.4	40 2.7	40 2.5				
	29 3.3	33 3.3	40 3.2	40 2.9	47 3.3	47 3.0				
	33 3.9	40 3.7	47 3.9	47 3.5	60 4.2	60 3.8				
40 4.5	47 4.4	60 4.5	60 4.5	77 4.5	77 4.5					
Tipo Centralina	2"- 08/E									

1 MPa = 10 bar

I valori di pressione in tabella possono essere aumentati del 10% per perdite dinamiche

**TABELLA VELOCITA' E POTENZE
CENTRALINE 2"- 08/E**



Start Elevator

01 012 / I

rev. 0

1/2

TIPO PISTONE	VELOCITA' PISTONE m/sec						
--------------	-------------------------	--	--	--	--	--	--

TRE ELEMENTI	176/3	0.51	0.60	0.68	0.76	0.82	0.90
	150/3	0.70	0.83	0.94	1.05
	127/3	0.97	1.15
	107/3
	98/3
	75/3
	58/3

DUE ELEMENTI	205/2	0.37	0.44	0.50	0.56	0.60	0.66
	170/2	0.54	0.64	0.73	0.82	0.88	0.96
	141/2	0.79	0.94	1.07
	120/2	1.09
	103/2
	85/2
	77/2
	60/2
	46/2

N O R M A L I	280	0.20	0.24	0.27	0.30	0.32	0.36
	238	0.28	0.33	0.37	0.42	0.45	0.49
	230	0.30	0.35	0.40	0.45	0.48	0.53
	200	0.39	0.46	0.53	0.59	0.63	0.70
	180	0.49	0.57	0.65	0.73	0.78	0.86
	150	0.70	0.83	0.94	1.05
	130	0.93	1.10
	120	1.09
	110
	100
	90

L/min	740	880	1000	1120	1200	1320
-------	------------	------------	-------------	-------------	-------------	-------------

potenza / pressione massima	kw Mpa	kw Mpa	kw Mpa	kw Mpa	kw Mpa	kw Mpa
	32 1.7	40 2.0	48 1.9	48 1.6	58 2.0	58 1.8
	40 2.3	48 2.3	58 2.4	58 2.1	66 2.2	66 2.0
	48 2.8	58 2.8	66 2.7	66 2.4	80 2.7	80 2.5
	56 3.3	66 3.3	80 3.2	80 2.9	94 3.3	94 3.0
	66 3.8	80 3.7	94 3.9	94 3.5	120 4.2	120 3.8
	80 4.5	94 4.4	120 4.5	120 4.5	154 4.5	154 4.5
Tipo Centralina	2"- 08/E2 2MP					

I valori di pressione in tabella possono essere aumentati del 10% per perdite dinamiche
1 MPa = 10 bar

